



F205 series rotator

- Rotary shaker for test tubes suitable for mixing different sized tubes via a “tumbling” motion and “rolling” motion
- Ideal to use in laboratories for preparation protocols
- Suitable for using with incubators, even refrigerated
- Adjustable angle rotation
- Digital speed control
- 0-90 min or ∞

Technical data		F205
Speed	rpm	tra 2 e 40
Timer	min	0 ÷ 90 o ∞
Display		digital
Rotation control		digital
Working temperature	°C	da +4 a +60
Power	W	80
Dimension LxWxH	mm	210 x270x240
Power	V/Hz	230/50
Weight	kg	3,2
Item		603.0129.26

ACCESSORIES

Rotating plate tube holder

Item	n. tubes	for ml
603.0129.41	48	1,5
603.0129.42	12	50

Rotating plate tube holder

Item	n. tubes	Ø mm
603.0129.43	20	9÷20

Rack tube holder for cell culture

Item	n. tube	Ø mm
603.0129.44	63	12
603.0129.45	63	16
603.0129.46	30	26



Roller

- Provides a rocking and rolling motion to test tubes
- Digital speed control
- 540 min digital timer
- Digital speed control with a resolution of 1 rpm
- Audible and visual alarm for motor overload
- Can be used with Bijoux, Universal containers, and bottles with diameters up to 135 mm

Technical data		F406	F409
Speed	rpm	5-60	5-60
Power	W	50	50
Timer	min	540	540
Amplitude excursion	mm	16	16
Rollers	n	6	9
Maximum load	kg	10	10
Internal dimension	mm	340x30	340x30
Total dimension LxWxH	mm	565x240x110	565x360x110
Environment	°C	da +4 a +60	da +4 a +60
Operating temperature	%	80	80
Power	V/Hz	230/50	230/50
Weight	kg	5,1	6,9
Item		603.0129.80	603.0129.82

Vortex mixer



Mix

- Ideal for mixing solutions in test tubes. It functions automatically by exerting pressure on the small stirring cup.
- Continuous operation can be selected by pushing the switch on the front panel. Stirring frequency can also be selected by the knob on the front panel.
- The Mixer is fitted with four small suction cups providing a firm grip on the work to.

Technical data		Mix
Rotary motion	mm	4+
Variable speed	rpm	100-3000
Safety class		0
Protection class	IP	41
Motor Power	W	30
Dimension LxWxH	mm	145×175×140
Power	V/Hz	220/240 – 50/60
Weight	Kg	1,9
Item		603.0129.02

ACCESSORIES



Clamp

Item

603.0129.06



Spring lock tube

Item

603.0129.10



Rod

Item

601.0125.01



FALC INSTRUMENTS s.r.l.

Via G. M. Compagnoni, 2 | 24047 Treviglio (BG) - Italy
+39 0363 304660 | falc@falcinstruments.it | falcinstruments.it